

MET132	1	2	3	4	5	# Ratings	Avg.					
Program the part manually (without the use of CAM software), Fall 2004	0%	1	5%	2	10%	11	52%	7	33%	21	4.1	
Program the part manually (without the use of CAM software), Fall 2005	0%	1	5%	7	35%	5	25%	7	35%	20	3.9	
Configure, and zero the machine axes to the part, Fall 2004	1	5%	1	5%	2	10%	10	48%	7	33%	21	4.0
Configure, and zero the machine axes to the part, Fall 2005	0%		0%	6	30%	4	20%	10	50%	20	4.2	
Program the machine for production of the part, Fall 2004	0%	1	5%	4	19%	6	29%	10	48%	21	4.2	
Program the machine for production of the part, Fall 2005	0%		0%	1	5%	14	70%	5	25%	20	4.2	
Use of offsets to modify part program, Fall 2004	4	19%	2	10%	9	43%	3	14%	3	14%	21	3.0
Use of offsets to modify part program, Fall 2005	1	5%	1	5%	7	35%	6	30%	5	25%	20	3.7
Perform calculations required for programming speeds and feeds, Fall 2004	5	24%	1	5%	4	19%	8	38%	3	14%	21	3.1
Perform calculations required for programming speeds and feeds, Fall 2005	8	40%	1	5%	3	15%	2	10%	6	30%	20	2.9
Safely adjust and cut the part in proper sequence, Fall 2004	1	5%	1	5%	0	0%	7	33%	12	57%	21	4.3
Safely adjust and cut the part in proper sequence, Fall 2005	0%	1	5%	1	5%	4	20%	14	70%	20	4.6	
Measure and inspect the part with calipers or micrometer to ensure the part is within tolerances, Fall 2004		0%	2	10%	4	19%	11	52%	4	19%	21	3.8
Measure and inspect the part with calipers or micrometer to ensure the part is within tolerances, Fall 2005	3	15%	1	5%	2	10%	3	15%	11	55%	20	3.9
To complete work in a timely fashion and keep all appointments, Fall 2004		0%	2	10%	0	0%	15	71%	4	19%	21	4.0
To complete work in a timely fashion and keep all appointments, Fall 2005		0%		0%		0%		0%	20	100%	20	5.0
Total	23	7%	15	5%	50	16%	98	32%	121	39%	307	3.9